



# ABB drives Product guide

Power and productivity  
for a better world™



# Smooth motor control and energy savings



## What is an AC drive?

An AC drive is an electronic device that is used to adjust the rotating speed or torque of a standard, electric AC motor. The electric motor, in turn, drives a load such as a fan, pump or conveyor.

AC drives are also referred to as frequency converters, variable frequency drives (VFD), variable speed drives (VSD), adjustable frequency drives (AFD), adjustable speed drives (ASD) or inverters.

## ABB - global market and technology leader in AC drives

ABB ([www.abb.com](http://www.abb.com)) is a leader in power and automation technologies that enable utility and industry customers to improve their performance while lowering environmental impact. ABB is the world's largest drives manufacturer. The ABB Group of companies operates in around 100 countries and employs more than 140,000 people.

## ABB in North America

Our roots within North America begin with the Westinghouse Electric Corporation, founded by George Westinghouse in 1886. A tireless inventor and businessman, Westinghouse's promotion of an alternating current (AC) system revolutionized the power industry.

Continuing to embrace the spirit of American industrialism, mining pioneer Henry Harnischfeger joined the ABB family tree in 1981, opening a new controls manufacturing facility in the heart of the Midwest. Today, a cornerstone of ABB Automation Products' business area resides within a state of the art production facility in New Berlin, Wisconsin. The Drives and Controls operations are responsible for the product development, applications design, manufacture and servicing of AC and DC drives, engineered drives and control systems, motors, generators, and power conditioning and power quality systems.

Electric motors consume about 65% of all electricity used throughout industry. Yet, less than 10% of those motors are fitted with a variable speed drive.

## Benefits of using AC drives

### Substantial energy savings

Rather than running an electric motor continuously at full speed regardless of the process, an electric drive allows the user to slow down or speed up the motor based on current demands.

### Optimal process control



An electric drive enables the process to achieve the right speed and torque while maintaining its accuracy. This contributes to more consistent quality and throughput of the end product.

### Reduced need for maintenance

Controlling the speed or torque of an electric motor means there is less wear and tear on the motor and the driven machine.

### Efficient system upgrade

An AC drive allows for the removal of valves, gears and belts. It also ensures network dimensioning based on a lower starting current.



## ABB drives common features

### Easy to select

Selecting a drive can be as simple as choosing the power rating, voltage and current through to more complex and detailed dimensioning and the addition of various options. See our guide on page 5 to get started.

### Easy to purchase

ABB drives are available from a large network of approved ABB partners. Please contact ABB for more details.

### Easy to install

The drives are simple to install, featuring a variety of mounting options from wall-mounted to cabinet mounted.

### Easy to operate

Once installed and commissioned, the drives are incredibly easy to operate. The user interface allows instant adjustments to speed or other more advanced parameters.

# Introducing the most extensive drives portfolio in the world

## **ABB low voltage AC drives**

Ranging from 0.25 hp to 7500 hp the ABB low voltage AC drives products is the widest available power offering from any manufacturer. ABB drives are the global benchmark signifying reliability, simplicity, flexibility, and ingenuity throughout the entire life-cycle of the drive.

Several of our drives feature energy consumption data calculators, which can be used to further analyze and tune a process for even greater energy savings.

The entire portfolio is supported by a selection of PC tools, fieldbus and communication options, as well as our global service offerings.

## **ABB micro drives**

### **Precise speed control and simple integration.**

ABB micro drives are suitable for many low power applications such as pumps, fans, and conveyors. Designed to be integrated into your machinery, they offer flexible mounting alternatives and straightforward setup with easy user interfaces and tools.

## **ABB machinery drives**

### **Premium motor control with hardware flexibility.**

ABB machinery drives can be configured to meet the precise needs of industry with a wide power and voltage range and both standard and optional features, including integrated safety and ready-made control programs for different applications.

## **ABB general purpose drives**

### **Simplified selection, installation and use.**

ABB general purpose drives offer simplicity and intelligence in one plug-and-play box. It's designed to control a wide range of standard drives applications, including pump, fan and constant torque use, such as conveyors.

## **ABB industrial drives**

### **The benchmark of performance, expertise and quality.**

ABB industrial drives offer scalability and performance to control a broad range of industrial applications with a range of options and features to fulfill even the most demanding requirements in the most extreme conditions. With a wide power and voltage range up to 5600 kW and 690 V, tune into precise performance and control no matter what industry you're in.

## **Industry specific drives**

Our industry specific ABB drives provide our customers with dedicated drive solutions for AC motor control used in industries such as HVAC and water and wastewater. Working closely with these industries, we have developed targeted functionality to help you improve your overall operating performance while also helping to reduce energy use. Built-in application macros in the drives help you easily setup and tailor processes.

## **ABB DC drives**

ABB's DC drive portfolio, from 5 to 24000 kW, provides the highest power-to-size ratio on the market. The drives are designed for most industries including metals, cement, mining, pulp and paper, printing, food and beverage, wire manufacturing, test rigs, ski lift and cranes. ABB DC drives are available as complete cabinets, panel drives, modules for cabinet assembly, and as retrofit kits. With built-in field exciters and integrated PLC's, they are the best DC drives choice for all new and retrofit applications.

To find more information please visit: [www.abb.com/drives](http://www.abb.com/drives)

# Choosing the right drive for your application

Step	Process	Action
1	<b>Identify the application</b> Identify the type of application and the likely demands of the drive.	Continue to step 2.
2	<b>Understand the load.</b> System inertia, required acceleration and deceleration rates, minimum and maximum speeds, overload requirements, etc. This information can often be determined by the performance of the existing motor.	Continue to step 3.
3	<b>Gather the motor nameplate data.</b> Power, Voltage, Current, Frequency(Hz), RPM, Insulation Class, etc.	Continue to step 4.
4	<b>Choose a drive</b> Match the data gathered in Steps 1 to 3 against the table of drive features on page 6 and 7. Select a drive that meets the motor requirements and has all the software features needed for the application.	Continue to step 5.
5	<b>Is the drive offered in the correct hp/amp rating?</b> The drive you choose must be able to supply the necessary current to the motor to produce the torque required. This includes normal and overload conditions. See selection table on page 6 and 7.	If yes, continue to step 6. If no, go to step 4.
6	<b>Is the drive offered in the correct enclosure and environmental ratings?</b> The drive you choose must be available in an enclosure style that will withstand the application's environment. It also must produce the required current at the application's altitude and ambient temperature. See selection table on page 6 and 7.	If yes, continue to step 7. If no, go to step 4.
7	<b>Does this drive have the features needed to meet the application's demands?</b> The drive you choose must have a feature set that matches the application. It also must have sufficient hardware (inputs and outputs, feedback, communications, etc.) to perform the application. See selection table on page 6 and 7.	If yes, continue to step 8. If no, go to step 4.
8	<b>Does this drive have the motor control performance to meet the application's demands?</b> The drive you choose must be able to produce the needed torque at the necessary speeds. It must also be able to control speed and torque depending on the application requirements.	If yes, continue to step 9. If no, go to step 4.
9	<b>Congratulations!</b> The ABB AC drive you have chosen has the features and performance needed for a successful application.	



# ABB drive selection table

Specification		Micro Drives			Machinery Drives		General Purpose Drives
		ACS55	ACS150	ACS250	ACS355	ACS850	ACS310
Voltage and power ranges		1-phase, 100 to 120 V: 0.25 to 0.5 hp (0.18 to 0.37 kW)	1-phase, 200 to 240 V: 0.5 to 3 hp (0.37 to 2.2 kW)	1-phase, 110 to 120 V: 0.5 to 1.5 hp (0.37 to 1.1 kW)	1-phase, 200 to 240 V: 0.5 to 3 hp (0.37 to 2.2 kW)	3-phase, 200 to 240 V: 0.5 to 30 hp (0.37 to 22 kW)	1-phase, 200 to 240 V: 0.5 to 3 hp (0.37 to 2.2 kW)
		1-phase, 200 to 240 V: 0.25 to 3 hp (0.18 to 2.2 kW)	3-phase, 200 to 240 V: 0.5 to 3 hp (0.37 to 2.2 kW)	1-phase, 200 to 240 V: 0.5 to 3 hp (0.37 to 2.2 kW) <sup>1)</sup>	3-phase, 200 to 240 V: 0.5 to 15 hp (0.37 to 11 kW)	3-phase, 380 to 500 V: 0.75 to 700 hp (1.1 to 560 kW)	3-phase, 200 to 240 V: 0.5 to 15 hp (0.37 to 11 kW)
			3-phase, 380 to 480 V: 0.5 to 5 hp (0.37 to 4 kW)	3-phase, 200 to 240 V: 0.5 to 5 hp (0.37 to 4 kW) <sup>8)</sup>	3-phase, 380 to 480 V: 0.5 to 30 hp 0.37 to 22 kW		3-phase, 380 to 480 V: 0.5 to 30 hp (0.37 to 22 kW)
				3-phase, 380 to 480 V: 0.5 to 10 hp (0.37 to 7.5 kW) <sup>1)</sup>			
				3-phase, 500 to 600 V: 1 to 15 hp (0.75 to 11 kW) <sup>1)</sup> 1 to 20 hp (0.75 to 15 kW) <sup>1)</sup>			
Protection classes	UL type 0/IP20	●	●	● <sup>8)</sup>	●	● <sup>3)</sup>	●
	UL type 1/IP21	–	–	–	○	–	○
	UL Type 12/IP54/IP55	–	–	–	–	–	–
	UL Type 4X/IP66/IP67	–	–	● <sup>1)</sup>	● <sup>1)</sup>	–	–
	UL type 3R	–	–	–	–	–	–
Mounting arrangements	Optimal for cabinet mounting	●	●	● <sup>8)</sup>	●	●	●
	Optimal for wall mounting	–	○	● <sup>1)</sup>	○	–	○
Programming	Parameter programming	●	●	●	●	●	●
	Sequence programming	–	–	–	●	– <sup>4)</sup>	–
Human-Machine interface	Basic control panel	–	–	–	○	–	○
	Assistant control panel	–	–	–	○, ● <sup>1)</sup>	●	○
	Integrated control panel	●	●	●	–	–	–
Motor Control		Scalar (V/Hz) selectable for linear (CT) or square function (VT)	Scalar (V/Hz) selectable for linear (CT) or square function (VT)	Scalar (V/Hz), enhanced V/Hz or open loop vector	Open loop vector, Scalar (V/Hz) and Closed loop control	Direct Torque Control (DTC) or Scalar (V/Hz)	Scalar (V/Hz) - Linear (CT), squared (VT), or user defined curve
Supply Option		–	–	–	–	6-pulse diode	–
Ambient temperature		-20 to 40 °C (-4 to 104 °F), 50 °C (122 °F) with 15% derate, 55 °C (131 °C) with 25% derate No frost allowed.	14 to 104 °F (-10 to +40 °C), 122 °F (+50 °C) No frost allowed.	<b>UL Type 0:</b> 14 to 104 °F (-10 to 40 °C), 122 °F (50 °C) with derate <b>UL type 4X:</b> 14 to 104 °F (-10 to 40 °C), No frost allowed.	14 to 104 °F (-10 to 40 °C), 122 °F (50 °C) No frost allowed.	14 to 104 °F (-10 to +40 °C), 131 °F (+55 °C), with derating No frost allowed.	14 to 104 °F (-10 to +40 °C), up to 50 °C with 10% derate No frost allowed.
Inputs and outputs	Digital inputs/outputs	3/0	5/0	4/0	5/1	6/2 <sup>5)</sup>	5/1
	Relay outputs	1	1	1 (+1 as option)	1	3	1
	Analog inputs/outputs	1/0	2/1	2/1	2/1	2/2	2/1
	Encoder feedback	–	–	–	○	○	–
Supported fieldbus protocols	Modbus RTU	–	–	●	○	○	●
	Profibus DP	–	–	–	○	○	–
	DeviceNet™	–	–	–	○	○	–
	ControlNet	–	–	–	○	○	–
	CANopen®	–	–	–	○	○	–
	Ethernet (Modbus/TCP)	–	–	–	○	○	–
	Ethernet (EtherNet/IP™)	–	–	–	○	○	–
	Ethernet (EtherCAT®)	–	–	–	○	○	–
	Ethernet (PROFINET IO)	–	–	–	○	○	–
	Ethernet (PowerLink)	–	–	–	–	–	–
EMC compliance (EN 61800-3)	C3, industrial use	○	●	○	●	●	●
	C2, commercial use (installation by EMC experts)	○	○	○	○	○ <sup>6)</sup>	○
	C1, commercial use	○ (conductive emissions)	○ (conductive emissions)	○	○ (conductive emissions)	–	○ (conductive emissions)
	Input reactors	–	○	○	○	○	○
	Output reactors	–	○	○	○	○	○
Brake chopper		–	●	Sizes 2 & 3 only	●	●	–
Suggested maximum motor cable length		98.5 to 164 ft (30 to 50 m)	98.5 to 196.9 ft (30 to 60 m)	328 ft (100 m)	98.5 to 196.9 ft (30 to 60 m)	328.1 to 984.3 ft (100 to 300 m)	98.5 to 196.9 ft (30 to 60 m)
Switching frequency		up to 16 kHz	up to 16 kHz	up to 32 kHz	up to 16 kHz	3 kHz (typical)	up to 16 kHz
Output frequency		0-130Hz (0/250Hz) <sup>10)</sup>	0 to 500 Hz	0 to 500 Hz	0 to 599 Hz	0 to 599 Hz	0 to 500 Hz
Overload capacity		150% for 60 s, 180% for 2s at start	150% for 60 s, 180% for 2 s	150% for 60 s, 175% for 2 s	150% for 60 s, 180% for 2 s	110% for 60 s, 150% for 60 s	110% for 60 s, 180% for 2 s
Number of preset speeds		1 <sup>10)</sup>	3	4	7	7	7
PC tools	Drive commissioning tool	○	–	–	○	○	○
	Drive offline programming tool	–	○	–	○	○	○
	Drive dimensioning tool	–	–	–	–	●	–
Approvals	UL, cUL, CE, C-Tick, EAC	●	●	●	●	●	●
	RoHS compliance	●	●	●	●	●	●

● Standard

○ Option

– Not Available

<sup>1)</sup> IP66 product variants

<sup>2)</sup> up to R2 as standard

<sup>3)</sup> G1/G2 frames IP00

<sup>4)</sup> Application Programming

<sup>5)</sup> DO are DIO and can be used as DI

<sup>6)</sup> Frame dependant

<sup>7)</sup> CC, PC, and PD product variants

<sup>8)</sup> IP20 variant

<sup>9)</sup> IP54 variant


<sup>10)</sup> Greater range when programmed with DriveConfig software

<sup>11)</sup> I/O can be expanded with optional modules


<sup>12)</sup> Eight digital outputs can be configured to be DI or DO

Specification		General Purpose Drives		Industrial Drives		
		ACS550	ACS800	ACS880	DCS800	
Voltage and power ranges		3-phase, 208 to 240 V: 0.75 to 100 hp (0.75 to 75 kW)	3-phase, 208 - 240V: 0.75 to 75 hp	3-phase, 208 - 240V: 0.75 to 100 hp (0.75 to 75 kW)	3-phase, 230 to 525 V: 5 to 3000 hp (4 to 2250 kW)	
		3-phase, 380 to 480 V: 1 to 550 hp (0.75 to 355 kW)	3-phase, 380 to 500 V: 2 to 2250 hp	3-phase, 380 to 500 V: 0.75 to 1850 hp	3-phase, 600 V: 200 to 3250 hp (150 to 1700 kW)	
		3-phase, 500 to 600 V: 1.5 to 150 hp	3-phase, 525 to 690V: 5 to 3000 hp	3-phase, 525 to 690V: 5 to 3250 hp	3-phase, 700 V: 500 to 4000 hp (400 to 3000 kW)	
					higher upon request	
Protection classes	UL type 0/IP20	–	●	●	●	
	UL type 1/IP21	●	●	●	–	
	UL Type 12/IP54/IP55	● <sup>1)</sup>	–	●	–	
	UL Type 4X/IP66/IP67	–	–	–	–	
	UL type 3R	● <sup>7)</sup>	–	–	–	
Mounting arrangements	Optimal for cabinet mounting	●	●	●	●	
	Optimal for wall mounting	Requires flange mount kit	Requires flange mount kit	Requires flange mount kit	–	
Programming	Parameter programming	●	●	●	●	
	Sequence programming	–	–	–	–	
Human-Machine interface	Basic control panel	○	–	–	–	
	Assistant control panel	●	●	●	●	
	Integrated control panel	–	–	–	–	
Motor Control		Scalar (V/Hz), Open and Closed Vector: Speed, Vector:Torque	Direct Torque Control (DTC), Scalar (V/Hz)	Direct Torque Control (DTC), Scalar (V/Hz)	–	
Supply Option		6-pulse diode	6-pulse diode, 12-pulse diode, Ultra Low Harmonic, Regenerative	6-pulse diode, 12-pulse diode, Ultra Low Harmonic, Regenerative	–	
Ambient temperature		5 to 122 °F (-15 to +50 °C) From 104 to 122 °F (+40 to +50 °C) with derating. No frost allowed.	5 to 122 °F (-15 to +50 °C) From 104 to 122 °F (+40 to +50 °C) with derating. No frost allowed.	5 to 131 °F (-15 to +55 °C) From 104 to 131 °F (40 to 55°C) with derating. No frost allowed.	32 to 104 °F (0 to 40 °C) From 104 to 131 °F (40 to 55°C) with derating. No frost allowed.	
Inputs and outputs	Digital inputs/outputs	6/0	6/0 <sup>11)</sup>	6/8 <sup>11,12)</sup>	8/7	
	Relay outputs	3 + (3 as option)	3 <sup>11)</sup>	3 <sup>11)</sup>	1	
	Analog inputs/outputs	2/2	3/2 <sup>11)</sup>	2/2 <sup>11)</sup>	4/2	
	Speed feedback	–	○	○	●	
Supported fieldbus protocols	Modbus RTU	●	○	●/○	○	
	Profibus DP	○	○	○	○	
	DeviceNet™	○	○	○	○	
	ControlNet	○	○	○	○	
	CANopen®	○	○	○	○	
	Ethernet (Modbus/TCP)	○	○	○	○	
	Ethernet (EtherNet/IP™)	○	○	○	○	
	Ethernet (EtherCAT®)	○	○	○	○	
	Ethernet (PROFINET IO)	○	○	○	○	
	Ethernet (PowerLink)	○	○	○	○	
EMC compliance (EN 61800-3)	C3, industrial use	–	○	○	●	
	C2, commercial use (installation by EMC experts)	●	○	○	○	
	C1, commercial use	○ (conductive emissions)	–	–	–	
Input reactors	Input reactors	● (built-in)	● (built-in)	● (built-in)	Required; supplied by others	
	Output reactors	○	–	–	–	
Brake chopper		● <sup>2)</sup>	●/○ <sup>6)</sup>	●/○ <sup>6)</sup>	Not applicable	
Suggested maximum motor cable length		328.1 to 656.2 ft (100 to 200 m)	5000 ft / 1000 ft <sup>6)</sup> (150m / 300m) <sup>6)</sup>	5000 ft / 1000 ft <sup>6)</sup> (150m / 300m) <sup>6)</sup>	Not applicable	
Switching frequency		up to 12 kHz	2 kHz (typical)	2.7 kHz (typical)	Not applicable	
Output frequency		0 to 500 Hz	0 to 300 Hz	0 to 500 Hz	Not applicable	
Overload capacity		150% for 60 s, 180% for 2 s	110% for 60s, 150% for 60s	110% for 60s, 150% for 60s	150% for 60 s, 150% for 30 s, 110% for 60 s	
Number of preset speeds		7	15	7	4	
PC tools	Drive commissioning tool	○	○	○	●	
	Drive offline programming tool	○	–	–	–	
	Drive dimensioning tool	○	○	○	○	
Approvals		UL, cUL, CE, C-Tick, EAC	●/– <sup>7)</sup>	●	●	
RoHS compliance		●	●	●	●	

# Horsepower Comparison Chart







General Purpose Drives

Industrial Drives

# ABB micro drives

## ACS55, 0.25 to 3 hp (0.18 to 2.2 kW)

### What is it?

The ACS55 drive is a component that can be integrated easily into existing panels, replacing contactors and motor starters. Its compact size is ideal for new installations or whenever speed control of AC induction motors is needed. For users new to drives, it is programmed using simple DIP switches and rotary dials.

The ACS55 drive meets the requirements of industrial end users, installers, machine builders and panel builders.



ACS55 frame sizes: A, B, C, D

Feature	Benefit	Result
Single phase supply	Suitable for single phase residential and commercial applications	Avoids cabling and installation costs associated with three-phase supplies
Slim design	Fits easily into a variety of cabinet designs	Cabinet size can be smaller or greater packing density can be achieved
Flexible installation alternatives	Screw or DIN rail mounting, sideways or side-by-side	One drive type can be used in various designs, saving installation costs and time
High switching frequency	Reduced motor noise	Does not disturb occupants of buildings
Integrated EMC filter as standard	High electromagnetic compatibility	Low EMC emissions in all environments
Easy configuration	Quick setup with DIP switches and trimmers	Substantial time savings. Minimal expertise needed.
DriveConfig kit PC tool	DriveConfig kit PC tool is used to set drive parameters and to upload the parameter set to a drive in seconds, even without a power connection to the drive. The DIP switches and trimmers on the front panel of the drive are disabled after using the DriveConfig kit. This prevents the end users from altering the drive configuration.	Time savings with multiple drives. Drive configuration protected from end user alterations.

For additional technical information, see the ACS55 Technical Catalog (3AUA0000163305) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB micro drives

## ACS150, 0.5 to 5 hp (0.37 to 4 kW)

### What is it?

The ACS150 drive is a component that can be incorporated into a wide variety of machines. It includes, as standard, all necessary functions and interfaces for typical applications with AC induction motors.

The ACS150 drive meets the requirements of new drive users, installers, machine builders and panel builders.



ACS150 frame sizes: R0, R1, R2

Feature	Benefit	Result
<b>User-friendly LCD control panel</b>	Clear alphanumeric display Easy setup and use	Time savings
<b>Flexible mounting alternatives</b>	Screw or DIN rail mounting, sideways or side-by-side	One drive type can be used in various designs, saving installation costs and time
<b>Integrated EMC filter</b>	High electromagnetic compatibility	Low EMC emissions in selected environments
<b>Built-in brake chopper as standard</b>	No need for an external brake chopper	Space savings, reduced installation cost
<b>Embedded potentiometer</b>	Easy to adjust output frequency	Time savings
<b>PID control</b>	Simple integration to process control	Cost savings as a result of less cabling
<b>FlashDrop tool</b>	FlashDrop is a hand held tool that is used to quickly and easily set drive parameters. FlashDrop tool uploads drive parameters directly to unpowered drives. The tool can copy parameters from one drive to another or between a PC and a drive.	Time savings, especially with multiple drives

For additional technical information, see the ACS150 Technical Catalog (3AUA0000085631) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB micro drives

## ACS250, 0.5 to 20 hp

### What is it?

The ACS250 micro drive offers easy to use and compact solutions for general purpose low power applications, such as: mixers, pumps, fans, conveyors, food and beverage. All variants include a built-in Modbus RTU serial communication to provide straightforward integration with control and monitoring systems. The drive's design and ease of setup benefit a broad range of industries.

Available in IP20 and IP66/NEMA4x enclosures.



ACS250, IP20 and IP66 enclosures

Feature	Benefit	Result
User-friendly LCD control panel	Clear alphanumeric display Easy setup and use	Time savings with programming and monitoring
Optional front mounted operator controls (IP66 variant)	Allows the drive to be mounted on the machine close to the operator	Cost savings with operator controls already mounted on the drive – no need for custom panels
Flexible mounting alternatives (IP20 variant)	Wall or DIN rail mounting without extra accessory kits	One drive type can be used in various designs, saving installation costs and time
PI control	Simple integration to process control	Cost savings with PLC functionality built into the drive
Slide-out help card (IP20 variant)	Ready reference, right on the drive	Time savings with setup and programming
Epoxy coated heatsink (IP66 variant)	Protects the heatsink from harsh washdown chemicals	Cost savings with extended life in the harshest environments
Integrated control panel	Quick setup, easy configuration and commissioning, rapid fault diagnosis	Substantial time savings locating faults and implementing repairs, thereby reducing maintenance costs
Enhanced V/Hz control for variable or constant torque applications	Optimized performance and energy savings for all applications	Limited inventory of one drive that can efficiently power both VT or CT applications
Flow through wiring (IP20 variant)	Facilitates panel layout, or contactor replacement, with power leads in at the top and motor cables out at the bottom	Time and cost savings for panel builders
Separate terminal cover (IP66 variant)	No need to expose sensitive electronics to the environment when connecting and commissioning the drive	Time savings with easy access to connection terminals
Built-in brake chopper as standard (sizes 2 & 3)	No need for an external brake chopper	Space savings, reduced installation cost
Safe torque off function (SIL3) as standard (600V only)	Built-in and certified function that is used for prevention of an unexpected startup and other stopping related functions	Reduces the need for external safety components. Helps machine builders to fulfill the requirements of Machinery Directive 2006/42/EC
Open loop vector speed control (600V only)	Precise speed control and automatic motor setup	Time and cost savings
High protection class variant (IP20 variant, up to 20 hp) (IP66 variant, up to 15 hp)	No need to design special enclosure for applications that require high ingress protection	Time and cost savings
CopyStick tool	CopyStick is used to quickly and easily set drive parameters. The tool uploads drive parameters directly to unpowered drives. The tool can copy parameters from one drive to another or between a PC and a drive.	Time savings, especially with multiple drives

For additional technical information, see the ACS250 product flyers (3AUA0000151036, 3AUA0000139676 or 3AUA0000139675) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB machinery drives

## ACS355, 0.5 to 30 hp (0.37 to 22 kW)

### What is it?

The ACS355 drive is user-friendly, with a wide range of built-in technology such as the safe torque off functionality and sequence programming, which reduce the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for speed and torque control of AC induction and permanent magnet motors.

The ACS355 drive meets the requirements of new drive users, installers, machine builders, system integrators and panel builders.



ACS355 frame sizes: R0, R1, R2, R3, R4 and IP66 variants

Feature	Benefit	Result
Same height and depth across power range	Effective space usage	Less engineering and installation time
Assistant control panel with Help functions	Quick setup, easy configuration and commissioning, rapid fault diagnosis	Substantial time savings locating faults and implementing repairs, thereby reducing maintenance costs
Scalar and vector control	Optimum performance depending on application	Ensures the end-product is produced cost efficiently
Sequence programming	Logic programming included as standard with PLC-like functions	Reduces components and wiring in control system
Integrated EMC filter	High electromagnetic compatibility	Low EMC emissions in selected environments
Built-in brake chopper as standard	No need for an external brake chopper	Space savings, reduced installation cost
Safe torque off function (SIL3) as standard	Built-in and certified function that is used for prevention of an unexpected startup and other stopping related functions.	Reduces the need for external safety components. Helps machine builders to fulfill the requirements of Machinery Directive 2006/42/EC.
Product variant for demanding environments with IP66/69K, UL Type 4X protection classes	No need to design special enclosure for applications that require high ingress protection. NSF certified.	Time and cost savings
Product variant for solar pumps	Drive converts PV energy from solar panels to AC current, it can be operated independent from the grid.	Long life time and reduced maintenance costs, energy use and pollution. Improved reliability in electricity supply.
FlashDrop tool	FlashDrop is used to quickly and easily set drive parameters. FlashDrop tool uploads drive parameters directly to unpowered drives. The tool can copy parameters from one drive to another or between a PC and a drive.	Time savings, especially with multiple drives

For additional technical information, see the ACS355 Technical Catalog (3AUA0000081917) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB machinery drives

## ACS850, 0.5 to 700 hp (0.37 to 560 kW)

### What is it?

ACS850 drives offers scalable motor control for use with a variety of motor types and programming flexibility to easily integrate the drive into your process.

Ideal for applications like cranes, extruders, conveyors, winders, pumps, fans, and mixers the ABB machinery drives family meets the production and performance needs of machine builders, system integrators, panel builders and end users.



Feature	Benefit	Result
<b>Compact size, side-by-side mounting</b>	Smallest frame size is only 93 mm (4 in) wide. More drives can be placed in the same cabinet	Optimum installation layout and efficient cabinet space usage. Space and cost savings.
<b>Modular design</b>	Many standard features and a wide range of options allow different system configurations.	Fits many application needs. Offers flexibility in system design.
<b>Drive programming and configuration</b>	Can replace relays and small PLCs with function block programming.	Lower investment cost. Higher flexibility in system design.
<b>Integrated safe torque off function (up to SIL 3)</b>	High SIL class means high reliability of the safety function. Can also be used to implement Emergency Stop without contactors.	Cost-effective and certified solution for safe machine maintenance. Fulfills IEC 61508, EN 62061 and EN ISO 13849-1 standards
<b>Direct torque control</b>	Accurate, dynamic and static speed and torque control. Excellent process control even without pulse encoder. High overload and high starting torque. Less noise during motor operation. Output frequency up to 500 Hz. Enhanced motor identification at standstill.	Improves product quality, productivity and reliability. Lower investment cost. Less maintenance. Suitable for use where audible noise is an issue. Applicable in high speed applications. Better process control due to more accurate identification. Motor identification without decoupling the load.
<b>Extensive configurable standard I/Os</b>	Optimized accessibility.	Lower cost. Fewer parts and installation work needed for cabinet assembly
<b>Energy efficiency counters</b>	Illustrates saved energy, CO2 emissions and energy cost in local currency using a baseline determined from the energy consumed when the fan or pump is used directly online	Shows direct impact on energy bill and helps control operational expenditure (OPEX)
<b>Advanced interface (user and machine) with Integrated real-time clock, with battery back-up</b>	Enables timed functions, ex: day/night	Energy and labor cost savings, eg pump only runs when needed, no human intervention to start/stop drive

For additional technical information, see the ACS850 Technical Catalog (3AUA0000178518) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB general purpose drives

## ACS310, 0.5 to 30 hp (0.37 to 22 kW)

### What is it?

The ACS310 drive is designed for variable torque applications, such as booster pumps and centrifugal fans. The drive contains a powerful set of features including built-in PID controllers and pump and fan control (PFC) that varies the drive's performance in response to changes in pressure, flow or other external data.

The ACS310 drive meets the requirements of new drive users, installers, machine builders, system integrators and panel builders.



ACS310 frame sizes: R0, R1, R2, R3, R4

Feature	Benefit	Result
<b>Same height and depth across power range</b>	Effective space usage	Less engineering and installation time
<b>Commissioning assistants</b>	Easy set up of parameters for PID controllers, real-time clock, serial communication, drive optimizer and drive startup	Time savings. Ensures all required parameters are set.
<b>Pump and fan control (PFC)</b>	One drive controls several pumps or fans. Auxiliary motors are driven according to the needed pump/fan capacity. One motor can be disengaged from the mains supply while others continue operating in parallel.	Saves cost of additional drives and external PLC. Longer life for pump or fan system while reducing maintenance time and costs. Maintenance can be carried out safely without stopping the process.
<b>Pump protection functions</b>	Pre-programmed features such as pipe cleaning, pipefill, inlet/outlet pressure supervision and detection of under- or overload	Reduces maintenance costs. Longer life for pump and fan system.
<b>PID controllers</b>	Varies the drive's performance according to the need of the application	Enhances production output, stability and accuracy
<b>Energy efficiency counters</b>	Illustrates saved energy, CO2 emissions and energy cost in local currency using a baseline determined from the energy consumed when the fan or pump is used directly online	Shows direct impact on energy bill and helps control operational expenditure (OPEX)
<b>Embedded Modbus EIA-485 fieldbus interface</b>	No need for external fieldbus options. Integrated and compact design.	Saves cost of an external fieldbus device. Increases reliability
<b>FlashDrop tool</b>	FlashDrop is a hand held tool that is used to quickly and easily set drive parameters. FlashDrop tool uploads drive parameters directly to unpowered drives. The tool can copy parameters from one drive to another or between a PC and a drive.	Time savings, especially with multiple drives

For additional technical information, see the ACS310 Technical Catalog (3AUA0000159910) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB general purpose drives

## ACS550, 1.0 to 550 hp (0.75 to 355 kW)

### What is it?

The ACS550 drive comes with built-in features that make it simple to install, commission, and operate. Ideal for variable and constant torque applications from pumps and fans to conveyors and mixers, as well as many other variable and constant torque applications. Several programming tools are available for easy dimensioning, commissioning, and maintenance making this one of our most versatile drives. The ACS550 drive meets the requirements of industrial end users, installers, machine builders, system integrators and panel builders.

### ACS550 Packaged Drives

The ACS550 drive is also available in various enclosure options (UL type 1, 12, and 3R) with circuit breaker and fused disconnects.



ACS550 frame sizes: R1, R2, R3, R4

Feature	Benefit	Result
Easy programming with parameter upload/download/back-up function	Quick setup and commissioning, simple configuration	Substantial time savings
Scalar, Sensorless Vector, Torque Control and Closed Loop Speed Control	Optimum performance depending on application	Increased process speed. Increased production capacity ensures end-product is produced cost efficiently.
Advanced interface (user and machine) with integrated real-time clock, with battery back-up	Enables timed functions, eg day/night	Energy and labor cost savings, eg pump only runs when needed, no human intervention to start/stop drive
Integrated EMC filter	No need for an external EMC filter	Cost saving
Patented swinging choke as standard	Reduced harmonics by up to 25%	Losses caused by harmonics in the supply network and grid connected equipment are reduced. Energy consumption is reduced and equipment lifetime extended.
Built-in brake chopper as standard up to 15 hp	No need for external brake chopper	Space savings, and lower installation cost, no need for an external brake chopper
Energy efficiency counters	Illustrates saved energy, CO <sub>2</sub> emissions and energy cost in local currency using a baseline determined from the energy consumed when the fan or pump is used directly online	Shows direct impact on energy bill and helps control operational expenditure (OPEX)
FlashDrop tool	FlashDrop is a handheld tool that is used to quickly and easily set drive parameters. FlashDrop tool uploads drive parameters directly to unpowered drives. The tool can copy parameters from one drive to another or between a PC and a drive.	Time savings, especially with multiple drives.

For additional technical information, see the ACS550 Technical Catalog (ACS550-PHTC01U-EN) or [www.abb.com/drives](http://www.abb.com/drives).



# ABB industrial drives

## ACS800

### What is it?

Our industrial drives are available both as complete AC drives and/or as modules to meet your requirements as a user, OEM or system integrator. Single Drive Module configurations contains a rectifier, DC link and an inverter in one single AC drive unit. They can be installed without any additional cabinet or enclosure and are available in wall-mounted, freestanding and cabinet-built constructions. They are specifically designed for industrial applications in process industries such as the pulp & paper, metals, mining, cement, power, chemical, and oil & gas.

The ACS800 series is available as wall-mount, cabinet-built, regenerative, low harmonic, air-cooled and liquid-cooled constructions.



Features	Benefits
<b>Compact size, everything integrated</b>	Less space and installation work required. No need to install extra components such as input chokes or EMC filter.
<b>Built in harmonic filter in all ACS800 drives</b>	Low harmonics, meaning less interference and less heating in cables and transformers. Filter also protects the drive from line side transients.
<b>Wide range of options available</b>	Standard solutions available from ABB to meet most customers application needs.
<b>Versatile braking options</b>	Optimal braking options are always available. No need for an external braking chopper thus reducing size and installation cost.
<b>User friendly customer interface</b>	Easy and fast commissioning and operation. Clear, alphanumeric display with start-up assistant that guides through the start-up procedure. Easy to use PC tools available for commissioning, maintenance, monitoring and programming.
<b>Versatile connections and communications</b>	Standard I/O covers most requirements. Connectable to commonly used fieldbuses.
<b>Extensive programmability</b>	Flexibility. Possible to replace relays or even a PLC in some applications. Two levels of programmability: 1. Parameter programming (standard) 2. Adaptive programming (free block programming) : standard feature, more blocks available as options, all I/Os are programmable
<b>Wide power and voltage range</b>	One product series can be used to meet all application needs, meaning less training and spare parts and standardized interface to drives.
<b>Wide range of robust enclosures available</b>	Industrial suitable solutions available for different environments including UL Type 1, UL Type 1 filtered, UL Type 12
<b>Robust main circuit design</b>	Suitable for heavy industrial use. Reliable. Long motor cables can be used without extra output filters. Advanced thermal model allows high overloadability.
<b>Extensive protection features</b>	Enhanced reliability, fewer process interruptions. Possibility to also protect motors and process. Several adjustable limits to protect other equipment included.
<b>Galvanic isolation of I/O</b>	Safe and reliable operation without separate isolators and relays.
<b>All terminals designed for industrial use</b>	Sufficient size even for large aluminum cables. No need for special tools in I/O cabling.
<b>Worldwide approvals: CE, UL, cUL, CSA, C-Tick, GOST R</b>	Products that can be used everywhere in the world.

For additional technical information, see the ACS800 Technical Catalogs (ACS800-PHTC01U-EN, ACS800-PHTC02U-EN, 3AFE68248531) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB industrial drives

## ACS880, 0.75 to 7500 hp (0.55 to 5600 kW)

### What is it?

The all-compatible ACS880 industrial drives are designed to tackle any of your motor-driven applications, in any industries, whatever the power range. Compatible with virtually all of your processes, automation systems, users and business requirements, the innovation behind the ACS880 drives is our drives architecture that simplifies operation, optimizes energy efficiency and helps maximize process output. The ACS880 series consists of single drives, multidrives and drive modules.



Feature	Benefit	Result
<b>Compact wall-mounted and cabinet-built drives and drives modules, with a wide power and voltage range</b>	Designed to provide customers across industries and applications with unprecedented levels of compatibility and flexibility. Drives are built to order with a wide range of options such as EMC filters, braking options and different enclosure variants.	Simplifies configuration and ordering process. Reduces training costs. Reduces service and maintenance costs.
<b>Drives built on ABB's common drives architecture</b>	A common architecture across the ACS880 drive family and future ABB drive families will simplify operation.	Reduces training time and costs
<b>Controls virtually any type of motor</b>	Our robust industrial drives ensure an energy efficient and reliable motor controller with significant cost savings for the user.	Reduces costs by improving energy efficiency.
<b>Enclosure classes range from IP00 to IP55</b>	Industrial suitable solutions available for different environments.	Saves time by providing a solution for every application and industry.
<b>Direct torque control (DTC) as standard</b>	Accurate, dynamic and static speed and torque control. Excellent process control even without pulse encoder. High overload and high starting torque. Less noise during motor operation. Output frequency up to 500 Hz. Enhanced motor identification at standstill.	Improves product quality, productivity and reliability. Reduces maintenance costs.
<b>Integrated safety features including safe torque off (STO) as standard</b>	Safe torque off is built-in as standard. An optional safety functions module provides extended safety functions.	Simplifies the configuration. Reduces product installation footprint. Reduces the need for additional external safety components.
<b>Application control programs</b>	Based on ABB's years of experience working with customers in various industries and applications, these ready-made application control programs are also flexible and allow you to configure up to four different configurations.	Enhances application usability and lowers energy consumption. Reduces the need for additional controllers. Increases productivity by protecting equipment.
<b>Drive application programming and IEC 61131-3 programming environment</b>	Makes programming of industry devices such as drives, PLC's, robots and human machine interfaces (HMI) easy using one integrated engineering suite. Suitable for engineering individual industry devices and for putting together entire automation projects. Customizable to meet the precise application needs based on IEC 61131-3.	Reduces the time needed to configure and program. Eliminates the need to install and maintain separate programs
<b>Intuitive control panel and common PC tool</b>	Intuitive, high-contrast and high-resolution display enabling easy navigation in multiple languages. The PC tool offers fast and harmonized setup, commissioning and monitoring for the whole drives portfolio.	Simplifies start-up, configuration and maintenance
<b>Primary control program – Identical software for the whole ACS880 series</b>	Includes built-in pre-programmed application macros that help set parameters for various functions.	Saves time during configuration and commissioning. Reduces amount of training required, especially with multiple drives.
<b>Removable memory unit</b>	The removable memory unit stores the software that includes user settings, parameter settings and motor data.	Easy to install, update and replace.
<b>Remote monitoring possibilities</b>	With a built-in web server, NETA-21 enables worldwide access to the drive via the Internet or local Ethernet network.	Increases productivity and reduces downtime with instant access to drives
<b>Communication with all major automation networks</b>	Fieldbus adapters enable connectivity with all major automation networks. The plug-in fieldbus adapter module can easily be mounted inside the drive.	Reduces wiring costs compared to traditional I/O connections. Simplifies the installation and commissioning process

For additional technical information, see the ACS880 Technical Catalogs (3AUA0000139403, 3AUA0000139404, 3AUA0000164773) or [www.abb.com/drives](http://www.abb.com/drives).

# ABB industrial drives

## DCS800, 5 to 4000 hp (4 to 3000 kW)

### What is it?

The DCS800 DC industrial drive from ABB combines a powerful controller with a thyristor power platform that has been proven in factories all over the world. The DCS800 boasts a wider power range than any other DC drive on the market. Special features make installation and configuration simple and allow you to customize the application to your needs. Both regenerative and non-regenerative drives are available. ABB also offers rebuild and upgrade kits specifically for retrofits to update the controls on existing DC drives. Panel drives are also available which include the DCS800 module and associated system components mounted and wired on a sub-panel.



Feature	Benefit	Result
<b>20 - 20,000 A; up to 5200 A in a single module package</b>	Widest available power range in the industry Highest power rating in the industry	The DCS800 will work regardless of the size of the load Saves the time and expense of paralleling drives
<b>250 - 1500 Vdc</b>	Widest supply voltage range in the industry	The DCS800 will work regardless of the size of the incoming voltage
<b>Adaptive Programming</b>	The user can easily customize the drive to their needs	The DCS800 will work in almost any application
<b>Uses ABB's R-Series of option modules</b>	Same plug-in options that are used on the ACS800 products	Reduced spare-part stocking cost; User familiarity simplifies startup and maintenance
<b>Compact design</b>	Highest power-to-size ratio in its class	Smaller enclosures; Makes system wiring faster and easier
<b>Common-sense programming</b>	Simplifies startup	Faster commissioning; easier to make adjustments
<b>Same footprint as DCS400 and most DCS500/600.</b>	Makes upgrades easy	Faster re-commissioning
<b>Controls can be replaced without replacing the power section</b>	Upgrade without replacing properly-functioning power components	Less costly upgrades
<b>DriveWindow Light</b>	Includes a commissioning wizard at no extra charge, making commissioning and adjustments easier	Faster commissioning; easier to make adjustments
<b>Multi-lingual control panel</b>	The DCS800 can be used in user's native language	Makes it easier to specify and order a drive
<b>Wide range of high-speed fieldbus modules</b>	The DCS800 can communicate with almost any PLC	Eliminates need to modify the PLC when retrofitting the drive, reducing cost
<b>ControlBuilder / IEC 61131 Option</b>	The drive is fully customizable	The DCS800 will work in highly unusual applications or when the customer needs some special firmware features
<b>DCS800-EP drive module and system components pre-wired on a panel</b>	System components are preselected, wired and tested	Less engineering, easier to implement, faster to commission
<b>DCS800-EP directly replaces FlexPak® 3000</b>	Same physical characteristics as the FlexPak® 3000. QuickStart commissioning assistant is similar to FlexPak® 3000. Detailed documentation provides information about replacement, potential issues, cross-references parameters and more.	Faster installation Faster commissioning; less downtime
<b>DCS800-EP are designed so components are accessible for maintenance</b>	Any part is able to be replaced quickly	Less down time
<b>DCS800-PC/-A0 provide a complete DC cabinet solution</b>	Integration is greatly simplified	Minimal engineering, easier to implement, faster to commission
<b>DCS800-PC is built domestically up to 500 hp</b>	Shorter lead time	Less time to wait for equipment to arrive
<b>Standard DCS800-A0 cabinets now available up to 3000 hp</b>	Included in the new catalog and price book	Faster and more efficient ordering process

For additional technical information, see the DCS800 Technical Catalog (DCS800-PHTC01U-EN) or [www.abb.com/drives](http://www.abb.com/drives).

FlexPak® 3000 is a registered trademark of Rockwell Automation, Inc.

# ABB industrial drives

## ACS2000, 300 to 3000 hp (250 to 2300 kW)

### What is it?

The medium voltage ACS2000 drive is an industrial all-rounder that perfectly adapts to a wide variety of standard applications across all industries. Various options and drive configurations allow you to choose the perfect match to increase your process and systems efficiency. Boundless versatility makes the ACS2000 fit perfectly into different conditions and environments all over the world. Benefit from the drive's state-of-the-art design and robust control platform that ensures reliable operation every day, every where.



ACS2000 Frame 1 with integrated disconnect

Feature	Benefit	Result
<b>Direct-to-line capability</b>	No transformer required Easy retrofit to fixed-speed motors Easy and fast commissioning	Reduced capital expenditure and overall cost of ownership
<b>Market specific design (NEMA/IEC)</b>	Market specific certifications (cUL, GOST-R) Compliance to local industry standards (IEC, NEMA, IEEE)	Drive configurations available for worldwide operations
<b>Active Front End (AFE)</b>	Power factor adjusted to compensate for reactive power Inherent low harmonic signature	Reduced energy loss in distribution system, avoiding the need for larger cables and utility penalties. Harmonic emissions compliant with all relevant standards.
<b>Direct Torque Control (DTC)</b>	Precise and reliable process control with superior performance	Increased productivity
<b>Multilevel topology</b>	Provides near sinusoidal current and voltage waveforms	Compatible with standard new or existing motors
<b>Voltage Source Inverter (VSI) topology</b>	Superior dynamic control performance	Safe ride through during supply voltage dips and better process control
<b>Compact size</b>	Requires less space in the electrical room	Frees up valuable floor space
<b>Regenerative option</b>	Maintain near unity power factor across the entire speed range	Reduces overall energy consumption
<b>Modular design</b>	Low parts count	Provides high reliability and low maintenance costs

Applications	
<b>Chemical, oil and gas</b>	Pumps, compressors, extruders, mixers and blowers
<b>Metals</b>	Fans and pumps
<b>Water</b>	Pumps
<b>Cement, mining and minerals</b>	Conveyors, crushers, mills, mine hoists, fans and pumps
<b>Marine</b>	Fans, pumps, compressors, propulsion and thrusters
<b>Power generation</b>	Fans, pumps, conveyors and coal mills
<b>Food and beverage</b>	Fans, pumps, sugar mills
<b>Other applications</b>	Test stands and wind tunnels

For additional technical information, see the ACS2000 Technical Data Catalog (ACS2000-PNTB01U-EN) or [www.abb.com/drives](http://www.abb.com/drives).

# Options Overview

## Fieldbus communications

Fieldbus adapter modules enable communication between drives, systems, devices and software. Our drives are compatible with a wide range of fieldbus protocols. The plug-in fieldbus adapter module can easily be mounted inside the drive.

- CANopen
- ControlNet
- DeviceNet
- EtherCAT
- Ethernet IP
- Ethernet Powerlink
- Modbus RTU
- Modbus TCP
- Profibus DP
- Profinet I/O
- PROFINsafe

## Driveware options and PC tools

ABB offers a variety of options that allow you to enhance your experience with our drives. These include various levels of control panels, parameter selecting/copy tools, engineering/optimization calculators, powerful integration/programming software, and helpful start-up/maintenance software.

- Automation Builder
- Drive composer
- DriveAnalyzer
- DriveAP
- DriveBrowser
- DriveConfig
- DriveMonitor
- DrivePM
- DriveSize
- DriveStudio
- DriveWindow / DriveWindow Light
- EnergySave calculator
- FanSave / PumpSave calculator
- Energy Calculator App

## Flexible product configurations

ABB understands every situation is unique. That is why we offer a wide range of options for our drives such as EMC filters, braking, enclosure, mounting, and cabling options.

### Enclosure Options

- UL type 0 (IP00)
- UL type 1 (IP21)
- UL type 1 filtered (IP42)
- UL type 4X (IP66)
- UL type 12 (IP55)
- UL type 12 (IP54)

### EMC Filters

- 1<sup>st</sup> Environment, Cat 1
- 1<sup>st</sup> Environment, Cat 2
- 2<sup>nd</sup> Environment, Cat 3

## Operator interface

Control panels feature intuitive use and easy navigation. Regardless of which control panel you choose, you are able to control the drive, set parameter values, copy settings from one drive to another, and more. The panel saves on commissioning and learning time by means of different assistants, making the drive simple to set up and use.

- Basic Control Panel
- Assistant control Panel
- Integrated or remote mounting options
- Potentiometer

## I/O options

Standard inputs and outputs can be extended by using optional analog and digital input/output extension modules. The modules are easily installed in the extension slots located on the control unit. Some ABB products also offer additional feedback devices, such as HTL pulse encoder, TTL pulse encoder, absolute encoder and resolver.

## Safety features

Safe torque off (STO) is used to prevent unexpected startup and in stopping-related functions, enabling safe machine maintenance and operation. With safe torque off activated, the drive will not provide a rotational field. This prevents the motor from generating torque on the shaft. It is a cost-effective and certified solution for safe machine maintenance by fulfilling IEC 61508, EN 62061 and EN ISO 13849-1 standards.

Additional safety features are available as options for our industrial drives family, including FSO-12, which includes six safety functions in one, easy to install module.

### Safety functions include:

- Safe stop 1 (SS1)
- Safe stop emergency (SSE)
- Safe brake control (SBC)
- Safely-limited speed (SLS)
- Safe maximum speed (SMS)
- Prevention of unexpected startup (POUS)

## Application control programs

ABB's industrial product family offers a range of ready-made programs to optimize application productivity and usability.

- Center Winder/Unwind
- Centrifuge Control
- Crane Control
- Inline Control
- Permanent Magnet Synchronous Motor
- Position Control
- Progressive Cavity Pump
- Pump Control
- System Application Software




## Remote monitoring

With a built-in web server and standalone datalogger, available remote monitoring options enables worldwide and secure access to drives.

**For more information on specific options and features, contact your local ABB Sales Representative or visit [www.abb.com/drives/connectivity](http://www.abb.com/drives/connectivity).**

# Applications Overview

Applications where to use	ABB micro drives			ABB machinery drives		ABB general purpose drives		ABB industrial drives		
	ACS55	ACS150	ACS250	ACS355	ACS850	ACS310	ACS550	ACS800	ACS880	DCS800
Pumps	●	●	●	●	●	●	●	●	●	●
Fans	●	●	●	●	●	●	●	●	●	●
Conveyors	●	●	●	●	●		●	●	●	●
Material handling machines	●	●	●	●	●		●	●	●	●
Exercise equipment	●	●	●							
Home appliances	●	●	●							
Gates, doors, barriers	●	●	●	●						
Compressors				●	●	●	●	●	●	●
Cutting machines, shears, saws				●	●		●	●	●	●
Extruders				●	●		●	●	●	●
Machine tools, mixers, stirrers		●	●	●	●		●	●	●	●
Spinning machines		●		●	●		●	●	●	●
Centrifuges				●	●		●	●	●	●
Processing lines		●	●					●	●	●
Grinders and mills								●	●	●
Cranes					●			●	●	●
Winches								●	●	●
Kilns								●	●	●



# ABB automation products

## Overview

### Motion controllers

ABB offers a wide range of motion control products to suit many different applications. Motion controllers are available in PCI format, as standalone units with USB, CANopen®, serial and Ethernet interfaces and as intelligent programmable drives for use in single or multi-axis systems.



### Servo drives

ABB offers a range of servo drives to cover many different applications. Its drives range from simple analog, fieldbus controlled drives, indexing drives, fully programmable motion drives and real-time Ethernet solutions based on the open standard Ethernet PowerLink and EtherCAT®. ABB motion drives control rotary and linear AC servo motors, and are available from 1 A single phase through to 580A three phase.




### Control panels

Our control panels offer a wide range of touchscreen graphical displays from 3.5" up to 15". They are provided with user-friendly configuration software that enables tailor-made customized Human Machine Interface (HMI) solutions. Rich sets of graphical symbols and the relevant drivers for ABB automation products are provided. Control panels for visualization of AC500 web server applications are available.



### Programmable Logic Controllers (PLC)

ABB's powerful flagship PLC offers a wide range of performance levels and scalability within a single simple concept where most competitors require multiple product ranges to deliver similar functionality. Web server integrated and IEC 60870-5-104 remote control protocol is available for all Ethernet versions. Additional products include PLCs customized for safety and extreme conditions.



### Servo motors

ABB's BSM series servo motors offer a wide choice of medium or low inertia models with winding options, feedback devices and gearheads to match. All ABB servo motors are designed for durability and ability to handle harsh environments.



### AC motors

ABB's low voltage AC motors are designed to save energy, reduce operating costs and enable demanding motor applications to perform reliably and without unscheduled downtime. General performance motors combine convenience and easy handling seamlessly with ABB's engineering expertise. Process performance motors provide the most comprehensive, versatile set of motors for the process industries and heavy-duty applications. Also included are motors that meet IEC 60034-30 IE3 Efficiency Levels for use in the United States.



# Life cycle services

## Your choice, your future

You made the choice to invest in the future of your business by purchasing an ABB drive. Let us help you make another easy choice: ABB Drive Care.

From install, to commissioning, to end-of-life support our portfolio of options will help maintain or improve your drives' performance and maximize their lifespan.

### Your choice, our business

Our business is helping you stay focused on your business. Whether your key concern is operational efficiency, life cycle management, rapid response, or all of the above, we have a service plan that will work for you throughout the entire lifetime of your drives.

Need help making the right choice? Let's talk about your future.

## Service offerings for your business

Your needs in service usually depend on your operation, priorities, and life cycle phase of your equipment. Here are the most typical service needs with some of our service product options that satisfy them:

### Is performance most critical to your operation?

Get optimal performance out of your machinery and systems.

#### Supporting services include:

- Training
- Inspections and Diagnostics
- Hardware and Control Upgrades
- Retrofits
- Workshop Repair
- Remote Care

### Need to extend your assets' lifetime?

Maximize your drive's lifetime with our services.

#### Supporting services include:

- Life Cycle Assessment
- Hardware and Control Upgrades
- Retrofits
- Replacement, Disposal and Recycling

### Is uptime your priority?

Keep your drives running with precisely planned and executed maintenance.

#### Supporting services include:

- Life Cycle Assessment
- Installation and Commissioning
- Spare Parts
- Preventive Maintenance
- Reconditioning
- Remote Care

### Is rapid response a key consideration?

If your drives require immediate action, our global network is at your service.

#### Supporting services include:

- Technical Support
- Drive Exchange
- On-site repairs
- Remote Support





# Additional Information

## QR codes

### Product websites



Micro drives website



Machinery drives website



General purpose drives website



Industrial AC drives website



Industrial DC drives website




Drives connectivity website



Medium Voltage Drives website



PLC website



Motion website



Motors website

### Product-specific documentation



ACS55



ACS150



ACS250



ACS355



ACS850



ACS310



ACS550



ACS880



ACS800



DCS800

# US District Sales Offices

## ARIZONA

### PHOENIX

4211 S. 43RD PLACE  
PHOENIX, AZ 85040  
PHONE: 602-470-0407  
FAX: 602-470-0464

## ARKANSAS

### CLARKSVILLE

706 WEST MAIN STREET  
CLARKSVILLE, AR 72830  
PHONE: 479-754-9108  
FAX: 479-754-9205

## CALIFORNIA

### LOS ANGELES

6480 FLOTILLA STREET  
COMMERCE, CA 90040  
PHONE: 323-724-6771  
FAX: 323-721-5859

### HAYWARD

21056 Forbes StReet  
Hayward, CA 94545  
Phone: 510-785-9900  
Fax: 510-785-9910

## COLORADO

### DENVER

3855 FOREST STREET  
DENVER, CO 80207  
PHONE: 303-623-0127  
FAX: 303-595-3772

## CONNECTICUT

### WALLINGFORD

65 SOUTH TURNPIKE ROAD  
WALLINGFORD, CT 06492  
PHONE: 203-269-1354  
FAX: 203-269-5465

## FLORIDA

### TAMPA / PUERTO RICO / VIRGIN ISLANDS

3906 EAST 11TH AVENUE  
TAMPA, FL 33605  
PHONE: 813-248-5078  
FAX: 813-241-9514

## GEORGIA

### ATLANTA

62 TECHNOLOGY DRIVE  
ALPHARETTA, GA 30005  
PHONE: 770-772-7000  
FAX: 770-772-7200

## ILLINOIS

### CHICAGO

340 REMINGTON BOULEVARD  
BOLINGBROOK, IL 60440  
PHONE: 630-296-1400  
FAX: 630-226-9420

## INDIANA

### INDIANAPOLIS

5525 W. MINNESOTA STREET  
INDIANAPOLIS, IN 46241  
PHONE: 317-246-5100  
FAX: 317-246-5110

## IOWA

### DES MOINES

1943 HULL AVENUE  
DES MOINES, IA 50313  
PHONE: 515-263-6929  
FAX: 515-263-6515

## MARYLAND

### BALTIMORE

7071A DORSEY RUN ROAD  
ELKRIDGE, MD 20175  
PHONE: 410-579-2135  
FAX: 410-579-2677

## MASSACHUSETTS

### BOSTON

6 PULLMAN STREET  
WORCESTER, MA 01606  
PHONE: 508-854-0708  
FAX: 508-854-0291

## MICHIGAN

### DETROIT

5993 PROGRESS DRIVE  
STERLING HEIGHTS, MI 48312  
PHONE: 586-978-9800  
FAX: 586-978-9969

## MINNESOTA

### MINNEAPOLIS

13098 GEORGE WEBER DR  
SUITE #400  
ROGERS, MN 55374  
PHONE: 763-428-3633  
FAX: 763-428-4551

## MISSOURI

### ST. LOUIS

13678 LAKEFRONT DRIVE  
EARTH CITY, MO 63045  
PHONE: 314-373-3032  
FAX: 314-373-3038

### KANSAS CITY

9810 INDUSTRIAL BLVD.  
LENEXA, KS 66215  
PHONE: 816-587-0272  
FAX: 816-587-3735

## NEW YORK

### AUBURN

ONE ELLIS DRIVE  
AUBURN, NY 13021  
PHONE: 315-255-3403  
FAX: 315-253-9923

## NORTH CAROLINA

### GREENSBORO

1220 ROTHERWOOD ROAD  
GREENSBORO, NC 27406  
PHONE: 336-272-6104  
FAX: 336-273-6628

## OHIO

### CINCINNATI

2929 CRESCENTVILLE ROAD  
WEST CHESTER, OH 45069  
PHONE: 513-771-2600  
FAX: 513-772-2219

## OHIO (continued)

### CLEVELAND

8929 FREEWAY DRIVE  
MACEDONIA, OH 44056  
PHONE: 330-468-4777  
FAX: 330-468-4778

## OKLAHOMA

### TULSA

9925 EAST ADMIRAL PLACE  
TULSA, OK 74116  
PHONE: 918-366-9320  
FAX: 918-366-9338

## OREGON

### PORTLAND

16201 SE 98TH AVENUE  
CLACKAMAS, OR 97015  
PHONE: 503-691-9010  
FAX: 503-691-9012

## PENNSYLVANIA

### PHILADELPHIA

103 CENTRAL AVENUE  
MT. LAUREL, NJ 08054  
PHONE: 856-840-8011  
FAX: 856-840-0811

### PITTSBURGH

159 PROMINENCE DRIVE  
NEW KENSINGTON, PA 15068  
PHONE: 724-889-0092  
FAX: 724-889-0094

## TENNESSEE

### MEMPHIS

4000 WINCHESTER ROAD  
MEMPHIS, TN 38118  
PHONE: 901-365-2020  
FAX: 901-365-3914

## TEXAS

### DALLAS

2920 114TH STREET SUITE 100  
GRAND PRAIRIE, TX 75050  
PHONE: 214-634-7271  
FAX: 214-634-8874

### HOUSTON

10355 W. LITTLE YORK ROAD SUITE 300  
HOUSTON, TX 77041  
PHONE: 281-977-6500  
FAX: 281-977-6510

## UTAH


### SALT LAKE CITY

2230 SOUTH MAIN STREET  
SALT LAKE CITY, UT 84115  
PHONE: 801-832-0127  
FAX: 801-832-8911

## WISCONSIN

### MILWAUKEE

1960 SOUTH CALHOUN ROAD  
NEW BERLIN, WI 53151  
PHONE: 262-784-5940  
FAX: 262-784-1215



# Contact us

For more information please contact your  
local ABB representative or visit:  
[www.abb.com/drives](http://www.abb.com/drives)

© Copyright 2015 ABB. All rights reserved.  
Specifications subject to change without notice.

3AUA0000181045/LVD-PHPG01U-EN REV M Effective 06/15/2015

Power and productivity  
for a better world™

